Product: Antenna-Railway-4N2WG

Railway Rooftop Antenna with 4x5G, 2xWLAN , 1xGNSS

Product Description

Railway Rooftop Antenna with 4x5G, 2xWLAN, 1xGNSS (active), EN50155, 3m Cable

Technical Specifications

Product Overview

Name:	Antenna-Railway-4N2WG

General Information

Scope of delivery:	7x Ant-Cable-Railway-01-Nm-TNCm-3 (3 m, N male to TNC male)

More Interfaces

GPS (global positioning system):	1x GPS / Galileo / GLONASS / BeiDou, Type: active, Frequency: 1560 - 1606 MHz (L1 Band), Gain: 5 dBi, VSWR ≤ 1,8 tyically, Impedance: 50 Ω, Radiation: Omnidirectional, Amplifier: 3.3 - 5.0 VDC, 8 mA at 3.3 VDC, 15 mA at 5.0 VDC, 25 dB gain typically, Connector: N-type female, 0.3m cable N-type male angle to amplifier with N-type female included

Radio technology

Modules

Description	Antenna Connector	Additional Radio Features	Frequency Band
Module 1	4x N-type female	Gain: 7 dBi at 700 MHz, 8 dBi at 1800 MHz, 10 dBi at 2600 MHz; VSWR ≤ 1,8 typically; Impedance 50 Ohm; Radiation pattern: Omnidirectional	700-1000 MHz, 1700-2700 MHz, 3100-3800 MHz
Module 3	2x N-type female	Gain: 7 dBi at 2.4 GHz, 8dBi at 5 GHz; VSWR ≤ 1,8; Impedance 50 Ω	WLAN: 2.4 GHz, 5 GHz

Ambient conditions

Degree of Protection when Installed:	IPX9k, IP6X
Operating temperature:	-60-+80 °C

Mechanical construction

Dimensions (WxHxD):	Antenna: Diameter 200 mm, Height 60mm
Weight:	1500 g
Housing Color:	black
Mating Side:	Bottom

Approvals

Basis Standard:	EN 50155, EN 50122-1, EN 50124, IEC 60068, IEC 61373, ISO20653, ISO 9227, EN 45545-2 2014/30/EU, 2006/28/EC, 2002/95/EC

Further Instructions

Certificates:	Certificates and further technical documentation in the downloads.

History

Update and Revision:	Revision Number: 0.30 Revision Date: 02-20-2026

Variants

Item #	Type	EAN Code
942998032	Antenna-Railway-4N2WG	4059759032271

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.