


## Type 4X Stainless Steel Two Door Floormount Enclosure *HN4 FM SS*

### Series

#### Continuous Hinge Door with Handle



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

### Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.
- 12" floor stands are welded to the enclosure.

### Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 13
  - IEC 60529, IP66

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable 10 gauge inner panel is finished in white powder coating.

### Accessories

- Additional Inner Panels
- Barrier Kits for Type 4 Floormount
- Drip Shield Kit
- Window Kits
- Lighting
- Door Stop Kit
- Mechanical Interlock
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

# New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

| 304 S.S.<br>Part Number | 316 S.S.<br>Part Number | Enclosure |       |       | Panel |       |
|-------------------------|-------------------------|-----------|-------|-------|-------|-------|
|                         |                         | H         | W     | D     | H     | W     |
| HN4FM604812SS           | HN4FM604812S1<br>6      | 60.13     | 48.06 | 12.69 | 56.00 | 44.00 |
| HN4FM604818SS           | HN4FM604818S1<br>6      | 60.13     | 48.06 | 18.69 | 56.00 | 44.00 |
| HN4FM606012SS           | HN4FM606012S1<br>6      | 60.13     | 60.06 | 12.69 | 56.00 | 56.00 |
| HN4FM606018SS           | HN4FM606018S1<br>6      | 60.13     | 60.06 | 18.69 | 56.00 | 56.00 |
| HN4FM726012SS           | HN4FM726012S1<br>6      | 72.13     | 60.06 | 12.69 | 68.00 | 56.00 |
| HN4FM726018SS           | HN4FM726018S1<br>6      | 72.13     | 60.06 | 18.69 | 68.00 | 56.00 |
| HN4FM727212SS           | HN4FM727212S1<br>6      | 72.13     | 72.06 | 12.69 | 68.00 | 68.00 |
| HN4FM727218SS           | HN4FM727218S1<br>6      | 72.13     | 72.06 | 18.69 | 68.00 | 68.00 |
| HN4FM727224SS           | HN4FM727224S1<br>6      | 72.13     | 72.06 | 24.69 | 68.00 | 68.00 |

Tags: **HN4FM, floormount, two door, stainless steel, Type 4X, NEMA 4X, instrument, hydraulic, pneumatic, 304, 316, continuous hinge, handle**

*Data subject to change without notice.*