

Door Stop Kit

NEW SIZES



Features

- Offered in 2 versions – standard and heavy duty
- Provides for door opening in fixed position as required.
- Prevents door swing that can occur in field maintenance situations.
- Minimum enclosure width of 20" for single door and 48" for two-door is required
- Door stop kit maintains NEMA 4x, 4, 3R and 12 ratings when installed correctly using the hardware and directions provided.
- Standard kit:
 - Ideal for most wallmount enclosure applications.
 - Manufactured in 12 gauge zinc plated steel.
 - Suitable for top and/or bottom installation.
- Heavy duty kit:
 - Designed for use with freestanding and floormount enclosures.
 - Can be used on certain heavy duty wallmount series - 1418, 1422, HN4WM or HWHK - providing the specific size does NOT have door stiffeners to interfere.
 - Manufactured in 10 gauge 316 stainless steel.
 - Designed for bottom of door installation only
 - Not compatible with enclosures with quarter turns located at bottom of doors.



Note: Kits not compatible on Eclipse enclosures with **swing panel** or **swing frame** accessories installed.

Part No.	Description
DSTOPK	Door stop kit
DSTOPKHD	Heavy duty door stop kit

Tags: door stop kit, stop, NEMA 4X, NEMA 12, heavy duty, wallmount, floormount, freestanding, 1418, 1422, HN4WM, HWHK

Data subject to change without notice.