

Specifications



Eaton B093-008-2E4U-V

8-Port Console Server with 4G LTE Cellular Gateway, Dual GB NIC, 4Gb Flash and Dual SIM

General specifications

PRODUCT NAME	Eaton Tripp Lite series serial console server
CATALOG NUMBER	B093-008-2E4U-V
UPC	037332206237
PRODUCT LENGTH/DEPTH	4.7 in
PRODUCT HEIGHT	1.4 in
PRODUCT WIDTH	5.1 in
PRODUCT WEIGHT	1.3 lb
WARRANTY	2 year limited
COMPLIANCES	RoHS CE Marked REACH FCC Compliant
CERTIFICATIONS	UL Listed C-Tick
PRODUCT TYPE	Serial console server

Product specifications

VOLTAGE RATING	• 100 VAC
	• 110 VAC
	• 120 VAC
	• 127 VAC
	• 200 VAC
	• 208 VAC
	• 220 VAC
	• 230 VAC
	• 240

NUMBER OF PORTS 8

FEATURES Flex Center

BTU RATING 39.2 BTU/Hr

LED INDICATORS 12 LEDs for Power, Heartbeat-Firmware Running, Serial Connectivity, Cellular Connectivity, Network Ports, and RSSI Signal Strength

MATERIAL OF CONSTRUCTION Metal

OPERATING TEMPERATURE RANGE -13° to 140°F (-25° to 60°C)

RELATIVE HUMIDITY 5% to 90% RH, Non-Condensing

STORAGE TEMPERATURE -40° to 167°F (-40° to 75°C)

AC POWER ADAPTER PLUG(S) CEE 7/16 Schuko
BS 1363 UK
AS/NZS 3112 Australia
NEMA 1-15P North America

AC POWER ADAPTER INPUT SPECS (V / HZ / A) 100-240V / 50/60Hz / 0.4A

AC POWER ADAPTER OUTPUT SPECS (V / A) 12V / 1.25A

AC POWER ADAPTER CORD LENGTH 4 ft

VOLTAGE COMPATIBILITY (VDC) 12

POWER CONSUMPTION 11.5 W

COLOR Black

AUTHENTICATION SUPPORTED RADIUS
TACACS
LDAP

PACKAGE CONTENTS Terminal block
DB9F to RJ45 crossover serial adapter
External power supply w/4 ft. cord (Input: 100-240V,

Resources

DRAWINGS

[KVM Switches and Consoles Visio Stencil](#)

[KVM Switches and Consoles Visio Stencil Preview](#)

MANUALS AND USER GUIDES

[Owner's Manual for B093-, B097- and B098-Series Console Servers \(English\)](#)

[Quick Start Guide for B093-004-2E4U-V and B093-008-2E4U-V \(Multi-language\)](#)

	50/60 Hz, 0.4A; Output: 12V 1.25A) (4) International plug adapters (North America, Europe, U.K., Australia) Quick Start Guide Dual-SIM cradle (2) Antenna blades Rack-mounting hardware B093-008-2E4U-V 8-Port Serial Console Server with 4G LTE Cellular Gateway, Dual GB NIC,4Gb Flash and Dual SIM (4) Rubber feet
IEEE STANDARDS SUPPORTED	802.3
PRODUCT FEATURES	Rackmountable Multi-User IP Remote Access
USB SPECIFICATION	USB 2.0 (up to 480 Mbps)
NETWORK SPEED	1 Gbps (Gigabit)
PRODUCT HIGHLIGHTS	Designed for standard Cat5e/6 patch cable when connecting to Cisco devices Built-in 4G LTE cellular modem with 2 SIM card slots provides out-of-band remote access Dual Gigabit Ethernet ports for primary network connection and automatic failover Easy installation on desktop or 19 in. racks using included mounting hardware 2-year limited warranty (Worldwide) Manage routers, UPS systems and other serial- based equipment from anywhere at any time 24/7
PACKAGING TYPE	Box
EXTERNAL POWER SUPPLY CERTIFICATIONS	FCC TUV C-Tick CE CB UL GS RoHS PSE cUL
POWER SOURCE TYPE	AC Adapter

PORT SELECTION	GUI
SIDEA CONNECTOR1	RJ45 (FEMALE)
SIDEB CONNECTOR1	USB A (FEMALE) RJ45 (FEMALE)
SIDEB CONNECTOR3	RJ45 (FEMALE) USB A (FEMALE)
	240
	110
	230
	120
	208
	125
	100
	127
VOLTAGE COMPATIBILITY (VAC)	200
	220
	100 VAC
	110 VAC
	120 VAC
	127 VAC
	200 VAC
	208 VAC
	220 VAC
	230 VAC

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

