

6ft (1.8m) USB Multi-Charging Cable, USB-A to Lightning/USB-C/Micro-USB, Apple MFi Certified, Braided Nylon Jacket; USB 3-in-1 Charger Cable/Cord

**Product ID:** LTCUB6GR



This USB multi-charging cable is a single-cable solution that makes it easy to charge and sync your Apple Lightning or Android devices.

Keep this USB to Micro-USB, USB-C or Lightning cable on hand for all your charging needs, instead of carrying multiple cables. The 3-in-1 cable makes it easy to switch between different device models and platforms. This cable can charge one device at a time.

Charge your devices from a USB wall charger, car charger, or power bank. The 6ft (1.8m) length enables greater reach, so you can access your device conveniently even while it's connected to a charger.

With a braided nylon jacket, this durable charging cable doesn't kink or tangle as easily as non-braided cables do. It's an excellent replacement for any of your charging cables.

To charge or sync a USB-C or Lightning mobile device, simply attach the corresponding connector to the Micro-USB connector and plug it into the device. To charge or sync over Micro-USB, plug just the middle connector of the cable into your mobile device. The charging cable facilitates one device at a time.

LTCUB6GR is Apple MFi certified for guaranteed compatibility and reliable performance with Apple devices.

## Certifications, Reports and Compatibility



## Applications

- Single USB cable with detachable connector ends for versatile compatibility
- Ideal for daily use and charging Apple or Android mobile devices
- Eliminate the need for multiple cables when traveling and charging on-the-go
- Micro-USB connector is compatible with legacy USB 2.0 devices

## Features

- **3-IN-1 CHARGING CABLE:** Connect an Apple Lightning, USB-C, or Micro-USB device to a USB wall charger or host; Charge and sync various mobile devices one at a time without swapping cables; Apple MFi Certified for iPhone/iPad (Up to 9th gen)
- **QUALITY CONSTRUCTION:** Durable Braided Nylon jacket prevents tangling and protects from wear; Aluminum-Mylar shield for enhanced EMI protection; Nickel-plated connectors with molded strain reliefs; Tested beyond 4,900 bending cycles at 25.4mm
- **APPLICATIONS:** Ideal for traveling and charging on-the-go; Attached Lightning and Type-C connectors eliminate the need for multiple cables; Braided outer jacket is robust and suitable for frequent use; Reduce cable clutter with a single versatile cable
- **PERFORMANCE:** Up to 2.4A Fast Charge; USB 480Mbps; USB-A to Lightning/Type-C/Micro-B; Apple MFi Certified; Length: 6ft (1.8m); Color: Silver; O.D.: 0.17in (4.4mm); Jacket: Braided Nylon w/Al-Mylar Shield; NOTE: USB-C video (DP Alt Mode) is not supported
- **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this USB Multi Charging Cable is backed for 2 years, including free lifetime 24/5 multi-lingual technical assistance; This 3-in-1 USB Charger Cord is available in 1m length (LTCUB1MGR)

### General

|                  |              |
|------------------|--------------|
| UPC              | 065030897587 |
| Package Quantity | 1            |
| Warranty         | 2 Years      |

### Power

|                |             |
|----------------|-------------|
| Power Source   | USB-Powered |
| Output Current | 2.4         |

### Physical & Environmental

|                 |          |
|-----------------|----------|
| Color           | Silver   |
| Material        | Aluminum |
| Connector Style | Straight |

|                       |                                 |
|-----------------------|---------------------------------|
| Wire Gauge            | 22 AWG                          |
| Conductor Type        | Stranded Copper                 |
| Cable Length          | 6.0 ft [1.8 m]                  |
| Cable OD              | 0.2 in [4.4 mm]                 |
| Product Length        | 6.0 ft [1.8 m]                  |
| Product Width         | 0.2 in [4.2 mm]                 |
| Product Height        | 0.2 in [5.7 mm]                 |
| Weight of Product     | 2.3 oz [66.0 g]                 |
| Operating Temperature | 0 to 60 (32&degF to 140&degF)   |
| Storage Temperature   | -20 to 60 (-4&degF to 140&degF) |
| Humidity              | 5%~95%                          |

---

#### Performance

|                            |                   |
|----------------------------|-------------------|
| Maximum Data Transfer Rate | 480Mbps           |
| Type and Rate              | USB 2.0 (480Mbps) |

---

#### Hardware

|                           |                                |
|---------------------------|--------------------------------|
| Active or Passive Adapter | Passive                        |
| Cable Shield Overlap      | Aluminium-Mylar Foil           |
| Connector Plating         | Nickel                         |
| Cable Jacket Material     | Braided                        |
| Cable Shield Material     | Aluminum-Mylar Foil with Braid |

---

#### Packaging & In-the-Box

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Included in Package | 1 - 6ft Lightning or USB-C or Micro-USB to USB Cable |
| Package Width       | 5.0 in [12.8 cm]                                     |
| Package Depth       | 3.2 in [81 mm]                                       |
| Package Height      | 1.3 in [32 mm]                                       |

Shipping (Package)  
Weight 2.6 oz [74 g]

---

**Connector(s)**

|                        |                             |
|------------------------|-----------------------------|
| Connector 1 (Quantity) | 1                           |
| Connector 1            | USB-A (480Mbps, 2.5W)       |
| Connector 2 (Quantity) | 1                           |
| Connector 2            | USB Micro-B (480Mbps, 2.5W) |
| Connector 3 (Quantity) | 1                           |
| Connector 3            | USB-C (480Mbps, 2.5W)       |
| Connector 4 (Quantity) | 1                           |
| Connector 4            | Apple Lightning             |

---

***\*Product appearance and specifications are subject to change without notice.***