

Specifications

Eaton B098-016-V



16-Port Console Server, USB Ports (2) - 4G LTE, Dual GbE NIC, 16Gb Flash, SD Card, Wi-Fi, Desktop/1U Rack, TAA



General specifications

PRODUCT NAME	Eaton Tripp Lite series serial console server
CATALOG NUMBER	B098-016-V
UPC	037332218070
PRODUCT LENGTH/DEPTH	1.75 in
PRODUCT HEIGHT	17 in
PRODUCT WIDTH	10 in
PRODUCT WEIGHT	0.0001 lb
WARRANTY	2 year limited
COMPLIANCES	TAA Compliant
PRODUCT TYPE	Serial console server

Product specifications

VOLTAGE RATING	• 100 VAC
	• 110 VAC
	• 120 VAC
	• 125 VAC
	• 127 VAC
	• 200 VAC
	• 208 VAC
	• 220 VAC
	• 230 VAC
	• 240

NUMBER OF PORTS	16
------------------------	----

FEATURES	Flex Center
-----------------	-------------

BTU RATING	51.2 BTU/Hr
-------------------	-------------

LED INDICATORS	10 LEDs for Power, Heartbeat-Firmware Running, Serial Connectivity, Cellular Connectivity, Network Ports, and Wifi
-----------------------	--

MATERIAL OF CONSTRUCTION	Metal
---------------------------------	-------

OPERATING TEMPERATURE RANGE	41° to 122°F (5° to 50°C)
------------------------------------	---------------------------

RELATIVE HUMIDITY	5% to 90% RH, Non-Condensing
--------------------------	------------------------------

STORAGE TEMPERATURE	-22° to 140°F (-30° to 60°C)
----------------------------	------------------------------

POWER CONSUMPTION	15 W
--------------------------	------

TAA COMPLIANCE	Yes
-----------------------	-----

COLOR	Black
--------------	-------

AUTHENTICATION SUPPORTED	RADIUS
---------------------------------	--------

PACKAGE CONTENTS	2.4 GHz SMA Wi-Fi diversity antenna Modular serial adapter, DB9 to RJ45 (M/F) Cisco rolled crossover serial adapter, DB9 to RJ45 (F/F) Cisco straight pinout (x2) loopback, black Quick Start Guide (2) C13 to NEMA 5-15P power cords, 6 ft. Rack-mounting hardware Cisco rolled modular serial adapter, DB9 to RJ45 (M/F) B098-016-V 16-Port Serial Console Server Coaxial cable antenna extender w/magnetic base, 10 ft.
-------------------------	---

Resources

DRAWINGS	KVM Switches and Consoles Visio Stencil Preview
	KVM Switches and Consoles Visio Stencil

MANUALS AND USER GUIDES	Owner's Manual for B093-, B097- and B098-Series Console Servers (English)
	Quick Start Guide for Console Servers (English)

	Crossover serial adapter, DB9 to RJ45 (F/F) Cisco rolled straight-through serial adapter, DB9 to RJ45 (F/F) (2) Cat5 patch cables, 6 ft. Straight-through serial adapter, DB9 to RJ45 (F/F) (2) 4G swivel-blade antenna Cisco rollover pinout (x1) loopback, red
IEEE STANDARDS SUPPORTED	802.3
PRODUCT FEATURES	Redundancy - Dual Power Inputs Rackmountable IP Remote Access Multi-User TAA Compliant
NETWORK SPEED	1 Gbps (Gigabit)
PRODUCT HIGHLIGHTS	Dual Gigabit Ethernet ports for primary network connection and automatic failover Manage routers, UPS systems and other serial-based equipment from anywhere 24/7 Designed for standard Cat5e/6 patch cable when connecting to Cisco devices Included Wi-Fi feature supports either Client or Access Point (WAP) mode Built-in 4G LTE cellular modem with dual SIM card slots for out-of-band remote access 2-year limited warranty (Worldwide)
PACKAGING TYPE	Box
PORT SELECTION	GUI CLI
POWER INPUT RECEPTACLE	IEC-320-C14
SIDEA CONNECTOR1	RJ45 (FEMALE)
SIDEB CONNECTOR1	RJ45 (FEMALE) RJ11 (FEMALE)
SIDEA CONNECTOR2	RJ11 (FEMALE)
SIDEB CONNECTOR2	RJ45 (FEMALE)
SIDEA CONNECTOR3	USB A (FEMALE)
SIDEB CONNECTOR3	SFP (FEMALE)

	RJ45 (FEMALE)
SIDEA CONNECTOR4	SD (FEMALE)
	125
	110
	120
	208
	230
	240
	127
	220
VOLTAGE COMPATIBILITY (VAC)	100
	200
	100 VAC
	110 VAC
	120 VAC
	125 VAC
	127 VAC
	200 VAC
	208 VAC
	220 VAC
	230 VAC

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

